

# PRODUCT INFORMATION PACKET

**marathon®**  
Motors

Model No: SCA2001A3123GAAD01

Catalog No: SCA2001A3123GAAD01

200kW, General Purpose Low Voltage IEC Motor, 3 phase, 2 Pole, 415V, B5, 50Hz, 95.0%, 315L Frame, TEFC  
Cast Iron IE2 Efficiency Motors



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2020 Regal Beloit Corporation, All Rights Reserved. MC017097E

**REGAL**

### Nameplate Specifications

|                            |         |                        |                             |
|----------------------------|---------|------------------------|-----------------------------|
| Output HP                  | 270 Hp  | Output KW              | 200.0 kW                    |
| Frequency                  | 50 Hz   | Voltage                | 415 V                       |
| Current                    | 319.2 A | Speed                  | 2979 rpm                    |
| Service Factor             | 1       | Phase                  | 3                           |
| Efficiency                 | 95 %    | Power Factor           | 0.92                        |
| Duty                       | S1      | Insulation Class       | F                           |
| Frame                      | 315L    | Enclosure              | Totally Enclosed Fan Cooled |
| Ambient Temperature        | 50 °C   | Drive End Bearing Size | 6316                        |
| Opp Drive End Bearing Size | 6316    | UL                     | No                          |
| CSA                        | No      | CE                     | Yes                         |
| IP Code                    | 55      |                        |                             |

### Technical Specifications

|                       |               |                       |                |
|-----------------------|---------------|-----------------------|----------------|
| Electrical Type       | Squirrel Cage | Starting Method       | Direct On Line |
| Poles                 | 2             | Rotation              | Bi-Directional |
| Mounting              | B5            | Motor Orientation     | Horizontal     |
| Drive End Bearing     | C3            | Opp Drive End Bearing | C3             |
| Frame Material        | Cast Iron     | Shaft Type            | Keyed          |
| Overall Length        | 1287 mm       | Frame Length          | 840 mm         |
| Shaft Diameter        | 65 mm         | Shaft Extension       | 140 mm         |
| Assembly/Box Mounting | SIDE          |                       |                |
| Outline Drawing       | 0231501395    | Connection Drawing    | 8442000085     |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:16/01/2020

4


3

Uncontrolled Copy

2

1

# OUTLINE




|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                    |                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|--------------------|
| DRAWING REVISION<br>A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | REVISION BY<br>GSR | DATE<br>15/11/2017 |
| ECO<br>ECO-0134564                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | APPROVED BY<br>JAY | DATE<br>15/11/2017 |
| ECO DESCRIPTION<br>NEW DRAWING RELEASE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                    |                    |
| <small>COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED.<br/>         PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF<br/>         REGAL BELOIT AMERICA, INC. (OWNER) AND CONTAINS OWNER'S PROPRIETARY<br/>         INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED,<br/>         BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED<br/>         TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT<br/>         AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL<br/>         BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN<br/>         RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.</small> |                    |                    |

|                           |                                                                |                              |
|---------------------------|----------------------------------------------------------------|------------------------------|
| DRAWN BY<br>GSR           |                                                                |                              |
| DATE<br>15/11/2017        |                                                                |                              |
| APPROVED BY<br>JAY        | DESCRIPTION<br><b>OUTLINE</b><br>FR-315L-2P-B5 MTG. TCA-RHS TB |                              |
| DATE<br>15/11/2017        |                                                                |                              |
| REFERENCE                 | MATERIAL                                                       | PROCESS/FINISH               |
| THIRD ANGLE<br>PROJECTION | SIZE<br>B                                                      | DRAWING NUMBER<br>0231501395 |
|                           |                                                                | SHEET<br>1 OF 1              |

|                       |                    |                    |                    |
|-----------------------|--------------------|--------------------|--------------------|
| DRAWING REVISION<br>A |                    | REVISION BY<br>SN  | DATE<br>13/01/2017 |
| ECO<br>ECO-0116390    | APPROVED BY<br>SBD | DATE<br>13/01/2017 |                    |
| ECO DESCRIPTION       |                    |                    |                    |
| NEW DRAWING RELEASE   |                    |                    |                    |

| GEOMETRIC TOLERANCE |         |      |
|---------------------|---------|------|
| LINEAR DIM          | >0-6    | ±0.1 |
|                     | >6-30   | ±0.2 |
|                     | >30-120 | ±0.3 |



NOTES:

1. PRESSURE-SENSITIVE ADHESIVE COATED PAPER ON THE BACK OF SELF-ADHESIVE.
2. AT THE END OF YELLOW, WORDS, SYMBOLS, LETTERS ARE BLACK, BORDER IS BLACK.
3. THE TOLERANCE OF THE LINEAR SIZE OF THE TOLERANCE WITHOUT THE TOLERANCE BY THE TABLE.

|             |  |  |  |                        |            |                |       |
|-------------|--|--|--|------------------------|------------|----------------|-------|
| <div></div> |  |  |  | DRAWN BY               |            | SN             |       |
|             |  |  |  | DATE                   |            | 16/12/2016     |       |
|             |  |  |  | APPROVED BY            |            | SBD            |       |
|             |  |  |  | DATE                   |            | 16/12/2016     |       |
|             |  |  |  | REFERENCE              |            |                |       |
| <div></div> |  |  |  | MATERIAL               |            | PROCESS/FINISH |       |
|             |  |  |  | THIRD ANGLE PROJECTION |            | <div></div>    |       |
|             |  |  |  | SIZE                   |            | DRAWING NUMBER |       |
|             |  |  |  | A                      | 8442000085 |                | SHEET |
|             |  |  |  |                        |            | 1 OF 1         |       |

8WD.442.2017

**REGAL**™ Regal Beloit America, Inc.

DESCRIPTION  
CONN DIAGRAM-NAMEPLATE

**Model No.** SCA2001A3123GAAD01

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |      |       |       | PF at __ load |       |       | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>d</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|------|-------|-------|---------------|-------|-------|----------------------------------------|----------------------------------------|----------------------------------------|
| 415      | Δ             | 50        | 200       | 270       | 319.2    | 2979       | 645.36    | IE2         | 5/4FL            | FL   | 3/4FL | 1/2FL | FL            | 3/4FL | 1/2FL | 5.3                                    | 1.8                                    | 2.7                                    |
|          |               |           |           |           |          |            |           |             | -                | 95.0 | 95.0  | 94.6  | 0.92          | 0.91  | 0.88  |                                        |                                        |                                        |
|          |               |           |           |           |          |            |           |             |                  |      |       |       |               |       |       |                                        |                                        |                                        |

|                                  |                                   |                                           |                                             |
|----------------------------------|-----------------------------------|-------------------------------------------|---------------------------------------------|
| Motor type                       | SCA                               | Degree of protection                      | IP 55                                       |
| Enclosure                        | TEFC                              | Mounting type                             | IM B5                                       |
| Frame Material                   | Cast Iron                         | Cooling method                            | IC 411                                      |
| Frame size                       | 315L                              | Motor weight - approx.                    | 1215 kg                                     |
| Duty                             | S1                                | Gross weight - approx.                    | 1260 kg                                     |
| Voltage variation *              | ± 10%                             | Motor inertia                             | 3.0257 kgm <sup>2</sup>                     |
| Frequency variation *            | ± 5%                              | Load inertia                              | Customer to Provide                         |
| Combined variation *             | 10%                               | Vibration level                           | 2.8 mm/s                                    |
| Design                           | N                                 | Noise level ( 1meter distance from motor) | 83 dB(A)                                    |
| Service factor                   | 1.0                               | No. of starts hot/cold/Equally spread     | 2/3/4                                       |
| Insulation class                 | F                                 | Starting method                           | DOL                                         |
| Ambient temperature              | -20 to +50 °C                     | Type of coupling                          | Direct                                      |
| Temperature rise (by resistance) | 70 [ Class B ] K                  | LR withstand time (hot/cold)              | 15/30 s                                     |
| Altitude above sea level         | 1000 meter                        | Direction of rotation                     | Bi-directional                              |
| Hazardous area classification    | NA                                | Standard rotation                         | Clockwise form DE                           |
| Zone classification              | NA                                | Paint shade                               | RAL 5014                                    |
| Gas group                        | NA                                | Accessories                               |                                             |
| Temperature class                | NA                                | Accessory - 1                             | -                                           |
| Rotor type                       | Aluminum Die cast                 | Accessory - 2                             | -                                           |
| Bearing type                     | Anti-friction ball                | Accessory - 3                             | -                                           |
| DE / NDE bearing                 | 6316 C3 / 6316 C3                 | Terminal box position                     | RHS                                         |
| Lubrication method               | Regreaseable                      | Maximum cable size/conduit size           | 1R x 3C x 240mm <sup>2</sup> /2 x M63 x 1.5 |
| Type of grease                   | Shell Gadus S5 V100 or Equivalent | Auxiliary terminal box                    | Available on Request                        |

I<sub>A</sub>/I<sub>N</sub> - Locked Rotor Current / Rated CurrentT<sub>d</sub>/T<sub>N</sub> - Breakdown Torque / Rated TorqueT<sub>A</sub>/T<sub>N</sub> - Locked Rotor Torque / Rated Torque
**NOTE**

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

\* Voltage, Frequency and combine variation are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

| Efficiency | Europe | China | India           | Aus/Nz | Brazil | Global IEC |
|------------|--------|-------|-----------------|--------|--------|------------|
| Standards  | -      | -     | IS 12615 : 2018 | -      | -      | -          |




Model No. SCA2001A3123GAAD01

| Enclosure | U<br>[V] | $\Delta$ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[kgm] | T<br>[Nm] | IE<br>Class | Amb<br>[°C] | Duty | Elevation<br>[m] | Inertia<br>[kg·m <sup>2</sup> ] | Weight<br>[kg] |
|-----------|----------|----------------------|-----------|-----------|-----------|----------|------------|------------|-----------|-------------|-------------|------|------------------|---------------------------------|----------------|
| TEFC      | 415      | $\Delta$             | 50        | 200       | 270       | 319.2    | 2979       | 65.81      | 645.36    | IE2         | 50          | S1   | 1000             | 3.0257                          | 1215           |

Motor Load Data

| Load Point   |       | NL   | 1/4FL | 1/2FL | 3/4FL | FL    | 5/4FL |
|--------------|-------|------|-------|-------|-------|-------|-------|
| Current      | A     | 61.7 | 100.4 | 174.6 | 251.1 | 319.2 |       |
| Torque       | Nm    | 0.0  | 160.5 | 321.5 | 483.1 | 645.4 |       |
| Speed        | r/min | 3000 | 2995  | 2990  | 2985  | 2979  |       |
| Efficiency   | %     | 0.0  | 91.4  | 94.6  | 95.0  | 95.0  |       |
| Power Factor | %     | 9.8  | 76.3  | 88.0  | 91.0  | 92.0  |       |


Performance vs Load Chart



Motor Speed Torque Data

| Load Point |       | LR     | P-Up   | BD     | Rated | NL   |
|------------|-------|--------|--------|--------|-------|------|
| Speed      | r/min | 0      | 600    | 2741   | 2979  | 3000 |
| Current    | A     | 1683.2 | 1514.8 | 1146.4 | 319.2 | 61.7 |
| Torque     | pu    | 1.8    | 1.5    | 2.7    | 1     | 0    |

Starting Characteristics Chart



NOTE Refer data sheet for applicable standard and tolerances on performance parameters


Issued By  
Issued Date

REGAL

Model No. SCA2001A3123GAAD01

| Enclosure | U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[rpm] | T<br>[kgm] | T<br>[Nm] | IE<br>Class | Amb<br>[°C] | Duty | Elevation<br>[m] | Inertia<br>[kg·m²] | Weight<br>[kg] |
|-----------|----------|---------------|-----------|-----------|-----------|----------|------------|------------|-----------|-------------|-------------|------|------------------|--------------------|----------------|
| TEFC      | 415      | Δ             | 50        | 200       | 270       | 319.2    | 2979       | 65.81      | 645.36    | IE2         | 50          | S1   | 1000             | 3.0257             | 1215           |

| Motor Speed Torque Data |         |                |                |                |                |                |    |     |
|-------------------------|---------|----------------|----------------|----------------|----------------|----------------|----|-----|
| Load                    | FL      | I <sub>1</sub> | I <sub>2</sub> | I <sub>3</sub> | I <sub>4</sub> | I <sub>5</sub> | LR |     |
| TWT Hot                 | s 10000 | 40             | 27             | 20             | 17             | 16             | 15 |     |
| TWT Cold                | s 10000 | 80             | 53             | 40             | 36             | 32             | 30 |     |
| Current                 | pu      | 1              | 2              | 3              | 4              | 4.5            | 5  | 5.3 |



NOTE Refer data sheet for applicable standard and tolerances on performance parameters

Issued By  
Issued Date

