

# PRODUCT INFORMATION PACKET

**marathon®**  
Motors

Model No: TCA5P52A3181GACD01

Catalog No: TCA5P52A3181GACD01

5.5 kW General Purpose Low Voltage IEC Motor, 3 phase, 1500 RPM, 415 V, 132S Frame, TEFC  
Cast Iron IE3 Efficiency Motors



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.  
©2020 Regal Beloit Corporation, All Rights Reserved. MC017097E

**REGAL**

### Nameplate Specifications

|                            |         |                        |                             |
|----------------------------|---------|------------------------|-----------------------------|
| Output HP                  | 7.50 Hp | Output KW              | 5.5 kW                      |
| Frequency                  | 50 Hz   | Voltage                | 415 V                       |
| Current                    | 10.3 A  | Speed                  | 1469 rpm                    |
| Service Factor             | 1       | Phase                  | 3                           |
| Efficiency                 | 89.6 %  | Power Factor           | 0.83                        |
| Duty                       | S1      | Insulation Class       | F                           |
| Frame                      | 132S    | Enclosure              | Totally Enclosed Fan Cooled |
| Ambient Temperature        | 50 °C   | Drive End Bearing Size | 6308                        |
| Opp Drive End Bearing Size | 6208    | UL                     | No                          |
| CSA                        | No      | CE                     | Yes                         |
| IP Code                    | 55      |                        |                             |

### Technical Specifications

|                       |               |                       |                |
|-----------------------|---------------|-----------------------|----------------|
| Electrical Type       | Squirrel Cage | Starting Method       | Direct On Line |
| Poles                 | 4             | Rotation              | Bi-Directional |
| Mounting              | B14B          | Motor Orientation     | Shaftdown      |
| Drive End Bearing     | 2z-C3         | Opp Drive End Bearing | 2z-C3          |
| Frame Material        | Cast Iron     | Shaft Type            | Keyed          |
| Overall Length        | 465 mm        | Frame Length          | 202 mm         |
| Shaft Diameter        | 38 mm         | Shaft Extension       | 80 mm          |
| Assembly/Box Mounting | Top           |                       |                |
| Outline Drawing       | 0213201187    | Connection Drawing    | 8442000085     |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/01/2020

4

3




Uncontrolled Copy

2

1

B

B

2X M25 CONDUIT  
ENTRY

A

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                    |                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|--------------------|
| DRAWING REVISION<br>A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | REVISION BY<br>NIV | DATE<br>17/12/2018 |
| ECO<br>ECO-0158679                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | APPROVED BY<br>SBD | DATE<br>17/12/2018 |
| ECO DESCRIPTION<br>NEW DRAWING RELEASE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                    |                    |
| <small>COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED.<br/>           PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF<br/>           REGAL BELOIT AMERICA, INC. (OWNER) AND CONTAINS OWNER'S PROPRIETARY<br/>           INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED,<br/>           BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED<br/>           TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT<br/>           AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL<br/>           BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN<br/>           RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.</small> |                    |                    |

|                           |                                                                                       |                              |
|---------------------------|---------------------------------------------------------------------------------------|------------------------------|
| DRAWN BY<br>NIV           |  |                              |
| DATE<br>17/12/2018        |                                                                                       |                              |
| APPROVED BY<br>SBD        | DESCRIPTION<br><b>OUTLINE</b><br>132S FR.- B14B MTG. MOTOR TYPE: TCA                  |                              |
| DATE<br>17/12/2018        |                                                                                       |                              |
| REFERENCE                 | MATERIAL                                                                              | PROCESS/FINISH               |
| THIRD ANGLE<br>PROJECTION | SIZE<br>B                                                                             | DRAWING NUMBER<br>0213201187 |
|                           |                                                                                       | SHEET<br>1 OF 1              |

4

3

2

1

| DRAWING REVISION    |             | REVISION BY | DATE       |
|---------------------|-------------|-------------|------------|
| A                   |             | SN          | 13/01/2017 |
| ECO                 | ECO-0116390 | APPROVED BY | DATE       |
|                     |             | SBD         | 13/01/2017 |
| ECO DESCRIPTION     |             |             |            |
| NEW DRAWING RELEASE |             |             |            |

| GEOMETRIC TOLERANCE |         |      |
|---------------------|---------|------|
| LINEAR DIM          | >0-6    | ±0.1 |
|                     | >6-30   | ±0.2 |
|                     | >30-120 | ±0.3 |



NOTES:

1. PRESSURE-SENSITIVE ADHESIVE COATED PAPER ON THE BACK OF SELF-ADHESIVE.
2. AT THE END OF YELLOW, WORDS, SYMBOLS, LETTERS ARE BLACK, BORDER IS BLACK.
3. THE TOLERANCE OF THE LINEAR SIZE OF THE TOLERANCE WITHOUT THE TOLERANCE BY THE TABLE.

|                        |  |            |                            |  |
|------------------------|--|------------|----------------------------|--|
| DRAWN BY               |  | SN         | Regal Beloit America, Inc. |  |
| DATE                   |  | 16/12/2016 | DESCRIPTION                |  |
| APPROVED BY            |  | SBD        | CONN DIAGRAM-NAMEPLATE     |  |
| DATE                   |  | 16/12/2016 | MATERIAL                   |  |
| REFERENCE              |  |            | PROCESS/FINISH             |  |
| THIRD ANGLE PROJECTION |  | A          | SIZE                       |  |
|                        |  |            | DRAWING NUMBER             |  |
|                        |  |            | 8442000085                 |  |
|                        |  |            | SHEET                      |  |
|                        |  |            | 1 OF 1                     |  |

**Model No.** TCA5P52A3181GACD01

| U<br>(V) | Δ / Y<br>Conn | f<br>(Hz) | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |    |       |       | PF at __ load |       |       | I <sub>a</sub> /I <sub>N</sub><br>[pu] | T <sub>a</sub> /T <sub>N</sub><br>[pu] | T <sub>b</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|----|-------|-------|---------------|-------|-------|----------------------------------------|----------------------------------------|----------------------------------------|
| 415      | Δ             | 50        | 5.5       | 7.5       | 10.3     | 1469       | 36.38     | IE3         | 5/4FL            | FL | 3/4FL | 1/2FL | FL            | 3/4FL | 1/2FL | 6.9                                    | 2.4                                    | 2.9                                    |
|          |               |           |           |           |          |            |           |             |                  |    |       |       |               |       |       |                                        |                                        |                                        |

|                                  |                            |                                           |                                            |
|----------------------------------|----------------------------|-------------------------------------------|--------------------------------------------|
| Motor type                       | TCA                        | Degree of protection                      | IP 55                                      |
| Enclosure                        | TEFC                       | Mounting type                             | IM B14B                                    |
| Frame Material                   | Cast Iron                  | Cooling method                            | IC 411                                     |
| Frame size                       | 132S                       | Motor weight - approx.                    | 84 kg                                      |
| Duty                             | S1                         | Gross weight - approx.                    | 87 kg                                      |
| Voltage variation *              | ± 10%                      | Motor inertia                             | 0.0446 kgm <sup>2</sup>                    |
| Frequency variation *            | ± 5%                       | Load inertia                              | Customer to Provide                        |
| Combined variation *             | 10%                        | Vibration level                           | 1.6 mm/s                                   |
| Design                           | N                          | Noise level ( 1meter distance from motor) | 61 dB(A)                                   |
| Service factor                   | 1.0                        | No. of starts hot/cold/Equally spread     | 2/3/4                                      |
| Insulation class                 | F                          | Starting method                           | DOL                                        |
| Ambient temperature              | -20 to +50 °C              | Type of coupling                          | Direct                                     |
| Temperature rise (by resistance) | 70 [ Class B ] K           | LR withstand time (hot/cold)              | 12/25 s                                    |
| Altitude above sea level         | 1000 meter                 | Direction of rotation                     | Bi-directional                             |
| Hazardous area classification    | NA                         | Standard rotation                         | Clockwise form DE                          |
| Zone classification              | NA                         | Paint shade                               | RAL 5014                                   |
| Gas group                        | NA                         | Accessories                               |                                            |
| Temperature class                | NA                         | Accessory - 1                             | -                                          |
| Rotor type                       | Aluminum Die cast          | Accessory - 2                             | -                                          |
| Bearing type                     | Anti-friction ball bearing | Accessory - 3                             | -                                          |
| DE / NDE bearing                 | 6308-2Z / 6208-2Z          | Terminal box position                     | TOP                                        |
| Lubrication method               | Greased for life           | Maximum cable size/conduit size           | 1R x 3C x 16mm <sup>2</sup> /2 x M25 x 1.5 |
| Type of grease                   | NA                         | Auxiliary terminal box                    | NA                                         |

I<sub>a</sub>/I<sub>N</sub> - Locked Rotor Current / Rated CurrentT<sub>b</sub>/T<sub>N</sub> - Breakdown Torque / Rated TorqueT<sub>a</sub>/T<sub>N</sub> - Locked Rotor Torque / Rated Torque
**NOTE**

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

\* Voltage, Frequency and combine variation are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

| Efficiency Standards | Europe | China | India           | Aus/Nz | Brazil | Global IEC |
|----------------------|--------|-------|-----------------|--------|--------|------------|
|                      | -      | -     | IS 12615 : 2018 | -      | -      | -          |




Model No. TCASP52A3181GACD01

| Enclosure | U   | $\Delta$ / Y | f    | P    | P   | I     | n     | T    | T     | IE   | Amb | Duty | Elevation | Inertia              | Weight |
|-----------|-----|--------------|------|------|-----|-------|-------|------|-------|------|-----|------|-----------|----------------------|--------|
| (V)       | Com | [Hz]         | [kW] | [hp] | [A] | [RPM] | [kgm] | [Nm] | Class | [°C] | S0  | S1   | 1000      | [kg·m <sup>2</sup> ] | [kg]   |
| TEFC      | 415 | $\Delta$     | 50   | 5.5  | 7.5 | 10.3  | 1469  | 3.71 | 36.38 | IE3  | 50  | S1   | 1000      | 0.0446               | 84     |

Motor Speed Data

| Load Point   | NL    | 1/4FL | 1/2FL | 3/4FL | FL   | 5/4FL |
|--------------|-------|-------|-------|-------|------|-------|
| Current      | A     | 4.5   | 5.0   | 6.3   | 8.1  | 10.3  |
| Torque       | Nm    | 0.0   | 8.9   | 18.0  | 27.1 | 36.4  |
| Speed        | r/min | 1500  | 1493  | 1485  | 1478 | 1469  |
| Efficiency   | %     | 0.0   | 85.1  | 89.6  | 89.6 | 89.6  |
| Power Factor | %     | 6.8   | 45.5  | 66.0  | 78.0 | 83.0  |


Performance vs Load Chart



Motor Speed Torque Data

| Load Point | LR    | P-Up | BD   | Rated | NL   |      |
|------------|-------|------|------|-------|------|------|
| Speed      | r/min | 0    | 300  | 1285  | 1469 | 1500 |
| Current    | A     | 71.0 | 63.9 | 40.1  | 10.3 | 4.5  |
| Torque     | pu    | 2.4  | 2.0  | 2.9   | 1    | 0    |

Starting Characteristics Chart



NOTE Refer data sheet for applicable standard and tolerances on performance parameters

Issued By  
Issued Date




Model No. TCASP52A3181GACD01

| Enclosure | U<br>(V) | $\Delta$ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[rpm] | T<br>[kgm] | T<br>[Nm] | IE<br>Class | Amb<br>[°C] | Duty | Elevation<br>[m] | Inertia<br>[kg·m <sup>2</sup> ] | Weight<br>[kg] |
|-----------|----------|----------------------|-----------|-----------|-----------|----------|------------|------------|-----------|-------------|-------------|------|------------------|---------------------------------|----------------|
| TEFC      | 415      | $\Delta$             | 50        | 5.5       | 7.5       | 10.3     | 1469       | 3.71       | 36.38     | IE3         | 50          | S1   | 1000             | 0.0446                          | 84             |

Motor Speed Torque Data

| Load     | FL | I <sub>1</sub> | I <sub>2</sub> | I <sub>3</sub> | I <sub>4</sub> | I <sub>5</sub> | LR  |     |
|----------|----|----------------|----------------|----------------|----------------|----------------|-----|-----|
| TWT Hot  | s  | 10000          | 41             | 28             | 25             | 16             | 15  | 12  |
| TWT Cold | s  | 10000          | 90             | 58             | 50             | 33             | 31  | 25  |
| Current  | pu | 1              | 2              | 3              | 4              | 5              | 5.5 | 6.9 |

Thermal Characteristics Chart



NOTE Refer data sheet for applicable standard and tolerances on performance parameters

Issued By  
Issued Date